

DESCRIPTION

This series of striplights has been designed for residential and light commercial applications. Choose from 15", 18", 24", 36", 48", and 96" lengths in a one lamp model, or 24", 36", 48" and 96" lengths in a two lamp model. A four lamp 48" fixture is also available. All units use T12 lamps.

CONSTRUCTION

Housing, cover and ends are die formed of 22 gauge cold rolled steel. Standard mounting holes and wiring knockouts are included. Can be stem, chain, or direct mounted; and can be hung individually or in continuous runs.

FINISH

Housing interior and exterior are finished in lighting grade white baked gloss enamel paint.

DIFFUSER



There is no diffuser for these fixtures. The fluorescent lamps are exposed.

ELECTRICAL



All ES units are wired with U.L. listed high power factor, rapid start, Class P, energy saving (ES) full light output (E) ballasts for 120 volt, 60 hertz A.C. operation. All non-ES units have trigger start normal power factor ballast. All (CW) units have cold weather ballasts with a minimum starting temperature of 0°F for standard lamps, ES lamps are not recommended for cold weather applications. Lampholders are rotating lock, medium bi-pin type. All fixtures are U.L. listed.

OPTIONS



Symmetric and asymmetric reflectors are available (contact factory). For ballast upgrades and options, refer to back of guide. Other voltages, listings, and ratings available on request (contact factory).



ST100 Series (1 Light)



ST200 Series (2 Lights)



ST440

ORDERING INFORMATION

DIMENSIONS

Model No.	Fluorescent Lamps	L	W	D	Mtg. Ill.
ST114RS	(1) T12 15"	15"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST115RS	(1) T12 18"	18"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST120RS	(1) T12 24"	24"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST130RS	(1) T12 36"	36"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST140RS	(1) T12 48"	48"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST140RSES	(1) T12 48"	48"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST140RSCW	(1) T12 48"	48"	2 ³ / ₄ "	3 ³ / ₄ "	113
ST140-8RSES	(2) T12 48" (Tandem)	96"	2 ³ / ₄ "	3 ³ / ₄ "	132
ST140-8RSCW	(2) T12 48" (Tandem)	96"	2 ³ / ₄ "	3 ³ / ₄ "	132
ST220RS	(2) T12 24"	24"	4 ⁵ / ₁₆ "	3 ¹ / ₁₆ "	114
ST230RS	(2) T12 36"	36"	4 ⁵ / ₁₆ "	3 ¹ / ₁₆ "	114
ST240RSES	(2) T12 48"	48"	4 ⁵ / ₁₆ "	3 ¹ / ₁₆ "	114
ST240-8RSES	(4) T12 48" (Tandem)	96"	4 ⁵ / ₁₆ "	3 ¹ / ₁₆ "	133
ST440RSES	(4) T12 48"	48"	8 ¹ / ₈ "	4 ⁵ / ₈ "	43